# neat.bar



Neat Bar is our compact and highly capable meeting device designed and engineered for Zoom. It's perfect for bringing superior-quality audio, and video to your huddle, focus and meeting spaces with up to 10 participants.

All you need is in the box, including mounts, cables and clear instructions. So it's easy for anyone to install and set-up, above or below one or two screens.

Our dedicated Neat Pad Controller comes included with Neat Bar, but you can choose to add an additional Neat Pad to be used as a scheduling display outside your meeting room.

### \* Supported in future software update

# **Neat Bar Specifications**

Camera LED
System LED
Accelerometer
Ambient light sensor
Sensors for temperature, humidity, CO2 and VOC (\*)
Table stand, wall mount and screen mount
Dual screen support
Kensington lock
Zoom Rooms software

#### **Audio**

Speakerbox for maximal tonal range with minimal distortion
Opposing drivers for vibration cancellation
Dedicated wide-angle ultrasonic tweeter
3 sensor mics
5 microphones angled in an end-fire array
Hardware accelerated audio processing
Beamforming
Echo cancellation
Noise suppression
Automatic gain control
Dereverberation

## **Video**

4x digital zoom
4056\*3040 (12 MP) capture resolution
120 degrees horizontal field of view
Automatic people framing (\*available in beta)
Hardware accelerated video encode and decode
Distortion correction
Noise reduction
Chromatic aberration correction
Automatic white balance and color correction
People video resolution: Up to 1080p / 30
Content video resolution: 720p / 60, 1080p / 30

## **Security**

Secure boot

Communications are established with 256-bit TLS encryption
Shared content is encrypted with AES-256 encryption
The Zoom Rooms app is secured with App Lock Code
As a native Zoom device Neat Bar supports all Zoom signaling and media encryption protocols.
Read more about Zoom security: https://zoom.us/docs/doc/Zoom-Security-White-Paper.pdf

#### \* Supported in future software update

## **Electrical and environmental requirements**

Speakerbox for maximal tonal range with minimal distortion Built-in power supply

100 - 240 V AC, 50 Hz to 60 Hz

Ambient operating temperature: 32° to 95° F (0° to 35° C)

Storage temperature: 5° to 149° F (-15° to 65° C)

Relative humidity: 20% to 80%

## **Networking & ports**

WiFi (\* available in beta)
AC Power (internal power supply)
Ethernet
USB-C for touch input (\* available in beta)
2x HDMI out for external screens
HDMI-in for Zoom sharing (1080p)

## Size & weight

Width: 21.9 inches (556 mm) Height: 3 inches (76 mm) Depth: 3 inches (76 mm) Weight: 3.75 pounds (1.7 kg)

#### What's in the box

Neat Bar

HDMI cable (6.5 feet / 2 meters) Ethernet cable (9.8 feet / 3 meters)

Power cord (9.8 feet / 3 meters)

Mount adapter, wall mount, screen mount and table stand


4x M6 (1.18 inches / 30mm) screw for VESA mount

4x M8 (1.18 inches / 30mm) screw for VESA mount for two-screen setup

2x spacer to secure parallel TV mount

## What you'll need

Zoom Rooms license Display with HD capability or better Internet connection





# **Neat Pad Specifications**

\* Supported in future software update

8-inch (diagonal) touch screen
1280 × 800 screen resolution
Anti glare, anti smudge coating
Ambient light sensor
Sensors for temperature, humidity, CO2 and VOC (\*)
Side LED Indicators
Speakers
2 microphones (\*)
Accelerometer
Wall mount and side mount
Kensington lock
Zoom Rooms software

## **Security**

Secure boot

The Zoom Rooms app is secured with App Lock Code

## **Electrical and enivornmental requirements**

Power over Ethernet (PoE): 802.3at PoE+ (Class 4/mode A)

56V DC 0.275 A

Ambient operating temperature: 32° to 95° F (0° to 35° C)

Storage temperature: 5° to 149° F (-15° to 65° C)

Relative humidity: 20% to 80%

## **Networking & ports**

WiFi

USB-C (reserved for future use) Ethernet (supports PoE)

Power adapter for AC (optional)

## Size & weight

Width: 7.8 inches (198 mm) Height: 1.7 inches (42 mm) Depth: 5 inches (127 mm) Weight: 1.15 pounds (520 g)


#### What's in the box

Neat Pad

2x Ethernet cable (9.8 feet / 3 meters + 16.4 feet / 5 meters) PoE power adapter

Mount adapter, side mount and wall mount


4x M4 (0.39 inches / 10 mm) screw for the wall mount 3x M4 (0.26 inches / 6.7 mm) screw for the side mount



#### Choose your mount

#### Follow the instructions









Single Dual Screen Wall Table Above Below

